

# P1M-6400P

## Server Powersupply



### Specification

<b>Model Name</b>	P1M-6400P								
<b>Size</b>	1U Single								
<b>Input Voltage</b>	100 - 240 V								
<b>Connectors</b>	<table> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-2</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-2</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 8 Pins	-1	SATA Power Connector	-2	4 Pin Power Connector	-2
Mother Board Connector 24 Pins	-1								
Core Voltage Connector 8 Pins	-1								
SATA Power Connector	-2								
4 Pin Power Connector	-2								

	Voltage	Amperage
<b>Ampere Rating</b>	+3.3 V	25.0A } Max.
	+5 V	35.0A } 45A
	+12 V	24.0A
	-12 V	0.8A
	-5 V	0.5A
	+5 VSB	2.0A

**Total Output** 400 W

**Compatible Chassis**

- RM-140L
- RM-1004
- RM-1021
- RM-160
- RM-115
- RM-13604



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)