

# FRS1200-50ERS

## Server Powersupply

### Specification

<b>Model Name</b>	FSP1200-50ERS																
<b>Size</b>	2U CRPS 1+1																
<b>Input Voltage</b>	100 V - 240 V																
<b>Connectors</b>	<table> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 4+4 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 6 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 6+2 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-7</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-10</td> </tr> <tr> <td>FDD Power Connector</td> <td>-1</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 8 Pins	-1	PCI Express Connector 4+4 Pins	-1	PCI Express Connector 6 Pins	-1	PCI Express Connector 6+2 Pins	-1	SATA Power Connector	-7	4 Pin Power Connector	-10	FDD Power Connector	-1
Mother Board Connector 24 Pins	-1																
Core Voltage Connector 8 Pins	-1																
PCI Express Connector 4+4 Pins	-1																
PCI Express Connector 6 Pins	-1																
PCI Express Connector 6+2 Pins	-1																
SATA Power Connector	-7																
4 Pin Power Connector	-10																
FDD Power Connector	-1																

	Voltage		Amperage	
<b>Ampere Rating</b>	+3.3 V	-	30.0A	} Max. 180W
	+5 V	-	30.0A	
	+12 V	-	81.0A	
	-12 V	-	0.3A	
	+5 VSB	-	5.0A	

**Total Output** 1200 W

**Compatible Chassis**  
 SR-105  
 RM-413  
 RM-423  
 RM-42612E  
 RM-43606E



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)