

FRS1200-50FS

Server Powersupply



Specification

Model Name	FSP1200-50FS																
Size	2U CRPS 1+1																
Input Voltage	100 V - 240 V																
Connectors	<table border="0"> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 4+4 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 6 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 6+2 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-7</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-10</td> </tr> <tr> <td>FDD Power Connector</td> <td>-1</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 8 Pins	-1	PCI Express Connector 4+4 Pins	-1	PCI Express Connector 6 Pins	-1	PCI Express Connector 6+2 Pins	-1	SATA Power Connector	-7	4 Pin Power Connector	-10	FDD Power Connector	-1
Mother Board Connector 24 Pins	-1																
Core Voltage Connector 8 Pins	-1																
PCI Express Connector 4+4 Pins	-1																
PCI Express Connector 6 Pins	-1																
PCI Express Connector 6+2 Pins	-1																
SATA Power Connector	-7																
4 Pin Power Connector	-10																
FDD Power Connector	-1																



	Voltage		Amperage	
Ampere Rating	+3.3 V	-	30.0A	} Max. 180W
	+5 V	-	30.0A	
	+12 V	-	81.0A	
	-12 V	-	0.3A	
	+5 VSB	-	5.0A	

Total Output 1200 W

Compatible Chassis	SR-105	RM-23808
	SR-108	RM-23524
	TW-115	RM-3001
	TW-125	RM-423
	RM-2003	RM-4002
	RM-2081	RM-4081
	RM-2081A	RM-4081E
	RM-2081B	RM-4262A
	RM-2082AH	RM-4382A
	RM-2082AN	RM-6502A
	RM-2142A	RM-6622A



Prime Source Technologies Pvt. Ltd

www.primesource.in