

# FSP250-50FEB

## Entrylevel Powersupply

### Specification

<b>Model Name</b>	FSP250-50FEB								
<b>Size</b>	1U Flex Single								
<b>Input Voltage</b>	100 V - 240 V								
<b>Connectors</b>	<table border="0"> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 4+4 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-4</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-2</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 4+4 Pins	-1	SATA Power Connector	-4	4 Pin Power Connector	-2
Mother Board Connector 24 Pins	-1								
Core Voltage Connector 4+4 Pins	-1								
SATA Power Connector	-4								
4 Pin Power Connector	-2								

	Voltage		Amperage	
<b>Ampere Rating</b>	+3.3 V	-	12.0 A	} Max. 80W
	+5 V	-	14.0 A	
	+12 V	-	18.0 A	
	-12 V	-	0.3 A	
	+5 VSB	-	2.5 A	

**Total Output** 250 W

**Compatible Chassis**

- RM-140L
- RM-1002
- RM-1003
- RM-1004
- RM-1021
- RM-238



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)