

FSP500-50FDB

Entrylevel Powersupply

Specification

Model Name	FSP500-50FDB										
Size	1U Single										
Input Voltage	100 V - 240 V										
Connectors	<table border="0"> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 4+4 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-3</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-3</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 8 Pins	-1	Core Voltage Connector 4+4 Pins	-1	SATA Power Connector	-3	4 Pin Power Connector	-3
Mother Board Connector 24 Pins	-1										
Core Voltage Connector 8 Pins	-1										
Core Voltage Connector 4+4 Pins	-1										
SATA Power Connector	-3										
4 Pin Power Connector	-3										

	Voltage		Amperage	
Ampere Rating	+3.3 V	-	14.0A	} Max. 90W
	+5 V	-	16.0A	
	+12 V	-	41.0A	
	-12 V	-	0.3A	
	+5 VSB	-	3.0A	

Total Output 500 W

Compatible Chassis

- RM-140L
- RM-1004
- RM-1021
- RM-160
- RM-115
- RM-13604
- RM-2003
- RM-3001



Prime Source Technologies Pvt. Ltd

www.primesource.in