

# FRS500-60MRB

## Server Powersupply

### Specification

<b>Model Name</b>	FSP500-60MRB														
<b>Size</b>	PS2 Mini Redundant 1+1														
<b>Input Voltage</b>	100 V - 240 V														
<b>Connectors</b>	<table border="0"> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td>-2</td> </tr> <tr> <td>Core Voltage Connector 4 Pins</td> <td>-1</td> </tr> <tr> <td>PCI Express Connector 6+2 Pins</td> <td>-2</td> </tr> <tr> <td>SATA Power Connector</td> <td>-6</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-5</td> </tr> <tr> <td>FDD Power Connector</td> <td>-1</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 8 Pins	-2	Core Voltage Connector 4 Pins	-1	PCI Express Connector 6+2 Pins	-2	SATA Power Connector	-6	4 Pin Power Connector	-5	FDD Power Connector	-1
Mother Board Connector 24 Pins	-1														
Core Voltage Connector 8 Pins	-2														
Core Voltage Connector 4 Pins	-1														
PCI Express Connector 6+2 Pins	-2														
SATA Power Connector	-6														
4 Pin Power Connector	-5														
FDD Power Connector	-1														

<b>Ampere Rating</b>	Voltage	Amperage	
	+3.3 V	-	} Max. 130W
	+5 V	-	
	+12 V	-	40.0A
	-12 V	-	0.5A
	+5 VSB	-	3.0A
	-5 V	-	0.3A

**Total Output** 500 W + 500 W

**Compatible Chassis** SR-105  
RM-4002  
RM-423



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)