

FSP700-80PSA

Server Powersupply



Specification

Model Name	FSP700-80PSA	Lorem ipsum
Size	PS2 Single	
Input Voltage	100 V - 240 V	

Connectors	Mother Board Connector 24 Pins	-1
	Core Voltage Connector 8 Pins	-1
	Core Voltage Connector 4+4 Pins	-1
	PCI Express Connector 6 Pins	-2
	PCI Express Connector 6+2 Pins	-2
	SATA Power Connector	-8
	4 Pin Power Connector	-7
	FDD Power Connector	-1

	Voltage	Amperage	
Ampere Rating	+3.3 V	-	24.0A
	+5 V	-	30.0A
	+12 V1	-	16.0A
	+12 V2	-	16.0A
	+12 V3	-	16.0A
	+12 V4	-	16.0A
	-12 V	-	0.5A
	+5 VSB	-	4.0A
	-5 VSB	-	0.5A

Max. 170W (for +3.3V, +5V, +12V1, +12V2)

Max. 56A (for +12V3, +12V4)



Total Output 700 W

Compatible Chassis

- HP-82
- HP-84B
- SR-105
- SR-108
- RM-2001
- RM-2003
- RM-2004
- RM-2005
- RM-3001
- RM-3003



Prime Source Technologies Pvt. Ltd

www.primesource.in