

FRS800-50FS

Server Powersupply

Specification

Model Name	FSP800-50FS																			
Size	2U CRPS 1+1																			
Input Voltage	100 V - 240 V																			
Connectors	Mother Board Connector 24 Pins	-1																		
	Core Voltage Connector 8 Pins	-1																		
	PCI Express Connector 4+4 Pins	-1																		
	PCI Express Connector 6 Pins	-1																		
	PCI Express Connector 6+2 Pins	-1																		
	SATA Power Connector	-4																		
	4 Pin Power Connector	-4																		
	FDD Power Connector	-1																		
Ampere Rating	<table border="0"> <tr> <td>Voltage</td> <td>Amperage</td> <td></td> </tr> <tr> <td>+3.3 V</td> <td>-</td> <td>25.0A } Max.</td> </tr> <tr> <td>+5 V</td> <td>-</td> <td>25.0A } 160W</td> </tr> <tr> <td>+12 V</td> <td>-</td> <td>65.0A</td> </tr> <tr> <td>-12 V</td> <td>-</td> <td>0.3A</td> </tr> <tr> <td>+5 VSB</td> <td>-</td> <td>4.5A</td> </tr> </table>	Voltage	Amperage		+3.3 V	-	25.0A } Max.	+5 V	-	25.0A } 160W	+12 V	-	65.0A	-12 V	-	0.3A	+5 VSB	-	4.5A	
Voltage	Amperage																			
+3.3 V	-	25.0A } Max.																		
+5 V	-	25.0A } 160W																		
+12 V	-	65.0A																		
-12 V	-	0.3A																		
+5 VSB	-	4.5A																		
Total Output	800 W + 800 W																			
Compatible Chassis	SR-105	RM-23808																		
	SR-108	RM-23524																		
	TW-115	RM-3001																		
	TW-125	RM-423																		
	RM-2003	RM-4002																		
	RM-2081	RM-4081																		
	RM-2081A	RM-4081E																		
	RM-2081B	RM-4262A																		
	RM-2082AH	RM-4382A																		
	RM-2082AN	RM-6502A																		
	RM-2142A	RM-6622A																		



Prime Source Technologies Pvt. Ltd

www.primesource.in