

# GW-CRPS2700D

## Server Powersupply



### Specification

<b>Model Name</b>	GW-CRPS2700D												
<b>Size</b>	2U CRPS 1+1												
<b>Input Voltage</b>	100 V - 240 V AC												
<b>Connectors</b>	<table border="0" style="width: 100%;"> <tr> <td>Mother Board Connector 20+4 Pins</td> <td style="text-align: right;">-1</td> </tr> <tr> <td>Core Voltage Connector 4+4 Pins</td> <td style="text-align: right;">-2</td> </tr> <tr> <td>Core Voltage Connector 8 Pins</td> <td style="text-align: right;">-2</td> </tr> <tr> <td>PCI Express Connector 6+2 Pins</td> <td style="text-align: right;">-8</td> </tr> <tr> <td>SATA Power Connector</td> <td style="text-align: right;">-4</td> </tr> <tr> <td>4 Pin Power Connector</td> <td style="text-align: right;">-8</td> </tr> </table>	Mother Board Connector 20+4 Pins	-1	Core Voltage Connector 4+4 Pins	-2	Core Voltage Connector 8 Pins	-2	PCI Express Connector 6+2 Pins	-8	SATA Power Connector	-4	4 Pin Power Connector	-8
Mother Board Connector 20+4 Pins	-1												
Core Voltage Connector 4+4 Pins	-2												
Core Voltage Connector 8 Pins	-2												
PCI Express Connector 6+2 Pins	-8												
SATA Power Connector	-4												
4 Pin Power Connector	-8												

Voltage	-	Amperage
<b>Ampere Rating</b> +3.3 V	-	25.0A
+5 V	-	25.0A
+12 V1	-	250.0A
-12 V	-	0.5A
+5 VSB	-	3.0A

**Total Output** 2700 + 2700 W

<b>Compatible Chassis</b>	SR-105	RM-23808
	SR-108	RM-23524
	TW-115	RM-3001
	TW-125	RM-423
	RM-2003	RM-4002
	RM-2081	RM-4081
	RM-2081A	RM-4081E
	RM-2081B	RM-4262A
	RM-2082AH	RM-4382A
	RM-2082AN	RM-6502A
	RM-2142A	RM-6622A



**Prime Source Technologies Pvt. Ltd**

[www.primesource.in](http://www.primesource.in)