

MRT-6320P

Server Powersupply



Specification

Model Name	MRT-6320P										
Size	PS2 Mini Redundant 1+1										
Input Voltage	90V / 264V										
Connectors	<table border="0"> <tr> <td>Mother Board Connector 24 Pins</td> <td>-1</td> </tr> <tr> <td>Core Voltage Connector 4+4 Pins</td> <td>-1</td> </tr> <tr> <td>SATA Power Connector</td> <td>-4</td> </tr> <tr> <td>4 Pin Power Connector</td> <td>-5</td> </tr> <tr> <td>FDD Power Connector</td> <td>-1</td> </tr> </table>	Mother Board Connector 24 Pins	-1	Core Voltage Connector 4+4 Pins	-1	SATA Power Connector	-4	4 Pin Power Connector	-5	FDD Power Connector	-1
Mother Board Connector 24 Pins	-1										
Core Voltage Connector 4+4 Pins	-1										
SATA Power Connector	-4										
4 Pin Power Connector	-5										
FDD Power Connector	-1										



Ampere Rating

Voltage		Amperage	
+3.3 V	-	18.0A	} Max. } 35A } Max. } 302W
+5 V	-	25.0A	
+12 V	-	16.6A	
-12 V	-	0.5A	
-5 V	-	0.5A	
+5 VSB	-	2.0A	

Total Output

320 W

Compatible Chassis

SR-105
RM-4001
RM-4002
RM-423



Prime Source Technologies Pvt. Ltd

www.primesource.in